

S-300XT

Keep Your Driver on
the Forklift



AVAILABLE OPTIONS

- **Extended Wrap Height**Increase the wrap heights of your loads. Replace the 203 cm (80") mast with a 279 cm (110") mast.
- **220 V - 50/60 Hertz 15 AMP**Adds a transformer to the machine.
- **Cold Environment**Operate in temperatures below -1 C to -18 C (+31 F to 0 F).
- **Corrosive Environment**Operate in corrosive environment. It is for machines with exposure to agents such as salt and fertilizer.
- **Click-n-Go® Remote Control**Start or stop the machine from the forklift or other location. Note: You can use the remote for multiple machines.
- **Wrap Arm Speed 1-15 RPM**Allows the wrap arm to rotate up to 15 RPM. Note: This option includes Power-Roller Stretch Plus and increases the pre-stretch to 250%.

SPECIFICATIONS

Performance

- **Peak Production Speed**Up to 30-40 loads/hr
- **Load Size Diagonal (Recommended)**1930 mm (76")
- **Maximum Load Wrap Height**2032 mm (80")
- **Maximum Load Weight**Floor Capacity

Load Handling

- **Wrap Arm Speed (Variable)**12 RPM
- **Wrap Arm Zone**2280 mm (90")
- **Wrap Arm Drive**3/4 HP TEFC

Performance Features

- XT Cut and Clamp 5.0®Standard
 - Auto Film Cut-Off™Not Applicable
 - Pallet Grip®Standard
 - Intelli-SensorStandard
 - Standard Film Width500 mm (20")
 - EZ Thread Film DeliveryStandard
 - Standard Pre-Stretch200%
 - Wrap ForceVariable (Electric)
 - Film Capacity250 mm Diameter - 500 mm Length
(10" Diameter - 20" Length)
 - Film Delivery SystemPower-Roller Stretch Plus
 - NEMA 12 EnclosureStandard
-

Weights and Size

- Approx. Shipping Weight1500 kg (3300 lbs)
 - Size3990 mm L
3660 mm W
3075 mm H
(157" L x 144" W x 121" H)
-

Service Requirements

- PneumaticNot Applicable
 - Dedicated Electric Service Req. US115 VAC, 20 AMP
 - Dedicated Electric Service Req. EU1L-PE-220V-50 Hz
-

Warranty

- Warranty Duration3 years
-